



ENTRUST



Sigma DS4-ES1 Instant Issuance System with Embosser

SOLUTION HIGHLIGHTS

Sigma: The next generation of instant card issuance

Entrust Sigma Instant Issuance Systems are specifically designed for today's cloud environments and give you the ability to easily issue the most secure financial cards in the world.


- **Simple:** From unboxing to issuing cards to managing your printer, we made sure Sigma was the most user-friendly card issuance solution in the world
- **Secure:** Our industry-leading issuance security architecture will keep your cards and your customers' data safe and secure at each step of the issuance process
- **Smart:** Forward-thinking technology and scalability allow you to expand your card issuance program as your needs evolve



KEY FEATURES & BENEFITS

The world's most user-friendly financial card printer

- Intuitive printer dashboard lets you see printer status, order supplies, check cleaning status, update firmware, or contact help – all from your mobile device
- Seamless self-service lets you access how-to videos and other helpful resources by simply scanning a QR code on the LCD display
- Variable LED light ring lets you incorporate brand colors or other customization into your ambient environment
- Pre-loaded ribbon cassettes make switching ribbons easy
- Optional multi-hopper enables multiple card designs from a single printer
- Removable card cassettes make securing card stock overnight a breeze





Sigma DS4-ES1 Instant Issuance System

Unmatched security

- Dual-control access with security locks protects card stock, supplies, and rejected cards, meeting Visa and Mastercard security requirements
- Card stock is easily removable for secure overnight storage
- Secure boot protects system from malware or virus on boot-up
- Trusted Platform Module (TPM) manages the printer's own TLS/SSL certificates and keys
- Connection and data sent between Entrust Adaptive Issuance software and printer is encrypted
- Customer data is encrypted and is not stored in the printer after printing is complete
- Our cloud-hosted instant issuance solutions are the only ones in the industry that are PCI-CP-certified

Flexible, scalable, and easily integrated into your IT environment

- Issuance capabilities include:
 - Full-color or monochrome direct to-card printing
 - Magnetic stripe encoding
 - Contact or contactless smart card encoding
- Choose on-premises or cloud-hosted deployment
- Embossed text with metallic tipping foil for an elegant look
- Add multi-hopper for multiple pre-designed card feeding
- A full suite of services is available to help ensure your instant issuance program runs smoothly at every one of your branches





Sigma DS4-ES1 Instant Issuance System

TECHNICAL SPECIFICATIONS

Standard Features & Supplies

| | |
|----------------------------|---|
| Print technology | Dye sublimation / resin thermal transfer |
| Print capabilities | Single- or dual-sided edge-to-edge, full-color, and monochrome printing |
| Print resolution | <ul style="list-style-type: none">• Standard mode: 300 dots per inch (dpi) (300 X 600, 300 X 1200) standard text, bar code, and graphics printing• TrueMatch™ printing technology. Ability to conform to ICC color workflow |
| Print speed | <ul style="list-style-type: none">• Single-sided color ribbon (YMCKT): up to 250 cards per hour (cph)• Double-sided color ribbon (YMCKT-KT): up to 180 cards per hour (cph)• Double-sided monochrome ribbon (black HQ): up to 500 cards per hour (cph)• 60 seconds to encode mag stripe, indent, emboss, and top the card• 64 seconds to print monochrome graphics, encode mag stripe, indent, emboss, and top the card• 78 seconds to print color graphics, encode mag stripe, indent, emboss, and top the card |
| Card capacity | Input hopper: 125 cards (based on 0.03-in. card thickness) Output hopper: 25 cards Reject holding tray: 10 cards Front exception card slot |
| Card sizes | Thickness: 0.010 inches to 0.040 inches (0.25mm - 1.016mm) Dimension: ID-1, CR-79 |
| Embossing/Indenting | <ul style="list-style-type: none">• 75-character embossing/indenting wheel, financial format per ID-1 ISO 7811-3• Single- or dual-sided• Mastercard security characters Helvetica® characters OCR-A1, OCR-B1 |
| Operating environment | Temperature: 60°F to 95°F (15°C to 35°C) Humidity: 20-80% RH - non condensing |
| Magnetic stripe encoding | ISO 7811 three-track support (high- and low-coercivity) JIS Type II single-track option |
| Smart card personalization | <ul style="list-style-type: none">• Contact and contactless smart card encoding for ISO 14443 A/B, ISO 15693, MIFARE®, MIFARE® DESFire® EV1/EV2• Single-wire connectivity Supports production of EMV® level-1 compliant card |
| Security features | <ul style="list-style-type: none">• Software-activated lock to secure card stock, supplies, and reject card hopper• TLS/SSL encryption, supports AES-256• Bolt-down ready• Secure cable lock (sold separately)• Concealed output hopper• Password-protected cabinet• Non-resettable card counter for auditing |
| LCD display languages | English, Spanish, German, Italian, and Japanese |
| Physical dimensions | <ul style="list-style-type: none">• Printer: L 17.4 in x W 8.9 in x H 9.0 in / 44.2 cm x 22.6 cm x 22.9 cm• Printer with optional multi-hopper: 23 in x 13.4 in x 16.2 in (58.4 cm x 34 cm x 41.1 cm)• Bottom module (indenting, embossing, topping, card output): 15 in. x 27.5 in. x 10.5 in. (38.1 cm x 69.9 cm x 36.8 cm) |



Sigma DS4-ES1 Instant Issuance System

| | |
|---------------------------------|--|
| Weight | Printer: 12.1 lbs (5.49 kg) Printer with multi-hopper: 30.9 lbs (14.02 kg) |
| Connectivity | USB, Ethernet, and WiFi <ul style="list-style-type: none"> • WiFi types: 802.11g/n • Authentication modes: None, WPA2 • Dual-band 2.4GHz & 5GHz |
| Driver operating system support | <ul style="list-style-type: none"> • Windows 10 version 1909 – 64-bit – enterprise, home, professional • Windows 10 – 32 bit – professional or enterprise |
| Warranties | 36 months |

Optional Features & Supplies

| | | |
|--------------------|---|------------|
| Multi-hopper | Six-compartment hopper, 125-card capacity each (750 cards total) | |
| Color ribbons | YMCKT | 500 images |
| | YMCKT-KT | 350 images |
| | KTT | 750 images |
| | YMCKL-KT | 300 images |
| | ST-KT | 500 images |
| | GT-KT | 500 images |
| Monochrome ribbons | Black, blue, red, green, silver matte, gold matte, silver metallic, and gold metallic: 1,500 images | |

Color ribbon guide: Y=Yellow, M=Magenta, C=Cyan, K=Black, T=Topcoat, S=Silver matte, G=Gold matte



Local Financial Solutions Provider

St. Louis, MO | Memphis, TN

1-888-345-8511

www.elliottdata.com

